

Smartdrive

APPLICATIONS

- Fan Coil Unit, Ventilation or Heater exchange system
- Retrofit replacement for Fan Coil Unit

SPECIFICATIONS

- Output power 45 Watts, 90Watts & 120 Watts
- Input voltage DC310V or 220VAC
- Variable speed range 300-1500rpm or multiple tap speed control
- Signal 0-6.5V VSP or 0-10V as option
- Feedback - Different Pulse number available
- One power drive two motors
- Constant speed or Constant torque
- Standard 100mm Center height, others Center heights optional
- CCC recognized

FEATURES

- No hall sensor with Field Oriented Control
- Patented Multiple speed design
- Over Heat and over Voltage protections
- Multiple protections for Over Current
- Special Locked Rotor protections design
- Resin construction ensure the protection level
- Integrated base or optional
- 10 Pole design, more stable operation and lower sound level

BENEFITS

- Maximum efficiency can achieve more than 80%
- Easy for material management due to few models
- No low frequency noise issue
- Compact design, integrated control box
- Advanced thermal design, Low temperature rise
- Programmable for Speed, torque, Maximum Current and Rotation
- Automatically slow down once overload, ensure the system operation uninterrupted
- 29 years of experience in BLDC motor and the reliability of the strict test, to ensure the reliability of the motor
- Easy for upgrading from AC motor to DC motor

REGAL REXNORD INDIA PVT. LTD.
Sector-11, Model Town, Faridabad, Haryana-121006
Tel: +91-129 7102300
Toll Free No.: 1800-313-7756
E-mail: Genteqindia_customercare@regalrexnord.com, Genteqindiasales@regalrexnord.com
Website: www.genteqindia.com | www.regalrexnord.com

A Regal Rexnord Brand
www.regalrexnord.com